

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 June 2006 (15.06.2006)

PCT

(10) International Publication Number
WO 2006/062246 A1

(51) International Patent Classification:
F04B 39/10 (2006.01)

(21) International Application Number:
PCT/JP2005/022992

(22) International Filing Date:
8 December 2005 (08.12.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-355157 8 December 2004 (08.12.2004) JP

(71) Applicant (for all designated States except US): MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka, 5718501 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MATSUMOTO, Tsuyoshi. IDE, Terumasa. MARUYAMA, Tomio. YAMAOKA, Masakazu.

(74) Agents: IWAHASHI, Fumio et al.; c/o Matsushita Electric Industrial Co., Ltd., 1006, Oaza Kadoma, Kadoma-shi, Osaka 5718501 (JP).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

[Continued on next page]

(54) Title: HERMETIC COMPRESSOR



(57) Abstract: A hermetic compressor including a discharge valve system in a cylinder. Discharge valve system (114) includes discharge reed (127) having opening/closing portion (132) and discharge reed holding portion (131), spring reed (128) having movable portion (134) and spring reed holding portion (133), and stopper (129) having regulation portion (138) and stopper holding portion (137). Discharge reed (127), spring reed (128) and stopper (129) are fixed in this order to pedestal (125) of valve plate (113). At spring reed bending portion (135) provided in movable portion (134), movable portion (134) is bent toward the direction of valve seat (124) and tip portion (136) is brought into contact with plate contact portion (126). Space is provided between movable portion (134) of spring reed (128) and opening/closing portion (132) of discharge reed (127), and both are not brought into close contact with each other. Thus, delay in closing discharge reed (127) can be prevented. As a result, since it is possible to prevent discharge reed (127) and spring reed (128) from being brought into close contact with each other, the deterioration of the refrigerating capacity can be suppressed and high efficiency can be achieved.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.